# PCT

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:		(11) International Publication Number:	WO 99/10585
D06L 1/00, C11D 1/00, D06L 1/02, 1/04, 1/12	A1	(43) International Publication Date:	4 March 1999 (04.03.99)
(21) International Application Number: PCT/U	S98/177	(74) Agents: SIBLEY, Kenneth, D. et Sajovec, P.A., P.O. Box 37428	
(22) International Filing Date: 27 August 1998	(27.08.9	8)	

HIS

(63) Related by Continuation (CON) or Continuation-in-Part (CIP) to Earlier Application

VS Not furnished (CON)
Filed on Not furnished

27 August 1997 (27.08.97)

(71) Applicant (for all designated States except US): MICELL TECHNOLOGIES, INC. [US/US]; NCSU Centennial Campus, Suite 3500, 1017 Main Campus Drive, Raleigh, NC 27606 (US).

(72) Inventors; and

(30) Priority Data: 08/921,620

(75) Inventors/Applicants (for US only): ROMACK, Timothy, J. [US/US]; 5810 Forest Ridge Drive, Durham, NC 27713 (US). CAUBLE, David, F. [US/US]; Apartment U, 2550 Glenwood Avenue, Raleigh, NC 27608 (US). McCLAIN, James, B. [US/US]; 7303-205 Calibre Park Drive, Durham, NC 27707 (US).

(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

**Published** 

With international search report.

(54) Title: DRY CLEANING METHODS AND COMPOSITIONS

(57) Abstract

A method for dry-cleaning articles such as fabrics and clothing in carbon dioxide comprises contacting an article to be cleaned with a liquid dry cleaning composition for a time sufficient to clean the fabric. The liquid dry-cleaning composition comprises a mixture of carbon dioxide, water, a surfactant, and an organic co-solvent. After the contacting step, the article is separated from the liquid dry cleaning composition. The method is preferably carried out at ambient temperature. The surfactant is preferably one that does not contain a CO<sub>2</sub>-philic group. The organic co-solvent is preferably an alkane and has a flash point above 140 °F.

# FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF .	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

10

15

20

25

30

35

#### DRY CLEANING METHODS AND COMPOSITIONS

This application is a continuation-in-part of commonly owned, copending patent application Serial No. 08/921,620, filed August 27, 1997, the disclosure of which is incorporated by reference herein in its entirety.

#### Field of the Invention

The present invention relates to methods and compositions for carrying out the dry-cleaning of fabrics (e.g., garments) in liquid carbon dioxide.

#### Background of the Invention

Commercial dry cleaning systems currently employ potentially toxic and environmentally harmful halocarbon solvents, such as perchloroethylene. Carbon dioxide has been proposed as an alternative to such systems in U.S. Patent No. 4,012, 194 to Maffei. A problem with carbon dioxide is, however, its lower solvent power relative to ordinary solvents.

German Patent Application DE3904514 A1, published August 23, 1990, describes a cleaning system combining various conventional anionic or nonionic surface active agents with supercritical CO<sub>2</sub>. The system described therein appears to combine the detergency mechanism of conventional surface active agents with the solvent power of supercritical fluid carbon dioxide. A carbon dioxide dry cleaning system effective for liquid carbon dioxide is not provided.

U.S. Patent No. 5,683,473 to Jureller et al. (see also 5,683,977 to Jureller et al.) describes a dry cleaning system utilizing carbon dioxide in liquid form in combination with surfactants that contain a functional moiety that is CO<sub>2</sub>-philic,

5

10

15

20

25

30

2

which surfactants are not conventionally used for detergent cleaning. Since there are numerous advantages to employing conventional surfactants (e.g., cost, ready availability, established regulatory approval, established toxicology, etc), it would be extremely desireable to have a dry cleaning system for liquid carbon dioxide that employs conventional surfactants that do not contain a CO<sub>2</sub>-philic group.

U.S. Patent No. 5,377,705 to Smith et al. describes a precision cleaning system in which a work piece is cleaned with a mixture of CO₂ and a co-solvent. Smith provides an entirely non-aqueous system, stating: "The system is also designed to replace aqueous or semi-aqueous based cleaning processes to eliminate the problems of moisture damage to parts and water disposal" (col. 4 line 68 to col. 5 line 3). Co-solvents that are listed include acetone and ISOPAR™ M (col. 8, lines 19-24). Use in dry cleaning is neither suggested nor disclosed. Indeed, since some water must be present in dry-cleaning, such use is contrary to this system.

In view of the foregoing, there is a continuing need for effective carbon dioxide-based dry cleaning systems.

#### **Summary of the Invention**

A method for dry-cleaning articles such as fabrics and clothing in carbon dioxide comprises contacting an article to be cleaned with a liquid dry cleaning composition for a time sufficient to clean the fabric. The liquid dry-cleaning composition comprises a mixture of carbon dioxide, water, a surfactant, and an organic co-solvent. After the contacting step, the article is separated from the liquid dry cleaning composition.

Preferably, the liquid dry cleaning composition is at ambient temperature, of about 0° C to 30° C. The surfactant is soluble in the co-solvent. The surfactant may or may not be soluble in the CO<sub>2</sub>. Hence, in one embodiment; the surfactant may contain a CO<sub>2</sub>-philic group. However, in the preferred embodiment, the surfactant does not contain a CO<sub>2</sub>-philic group. Hence, an advantage of the present invention is that, by proper use of the co-solvent, conventional surfactants may be employed in a liquid carbon dioxide dry cleaning system.

٠.,

5

10

15

20

25

30

3

#### **Detailed Description of the Invention**

The term "clean" as used herein refers to any removal of soil, dirt, grime, or other unwanted material, whether partial or complete. The invention may be used to clean nonpolar stains (*i.e.*, those which are at least partially made by nonpolar organic compounds such as oily soils, sebum and the like), polar stains (*i.e.*, hydrophilic stains such as grape juice, coffee and tea stains), compound hydrophobic stains (*i.e.*, stains from materials such as lipstick and candle wax), and particulare soils (*i.e.*, soils containing insoluble solid components such as silicates, carbon black, etc.).

Articles that can be cleaned by the method of the present invention are, in general, garments and fabrics (including woven and non-woven) formed from materials such as cotton, wool, silk, leather, rayon, polyester, acetate, fiberglass, furs, etc., formed into items such as clothing, work gloves, rags, leather goods (e.g., handbags and brief cases), etc.

Liquid dry-cleaning compositions useful for carrying out the present invention typically comprise:

- (a) from 0.02, 0.05 or 0.1 to 5 or 10 percent (more preferably from .1 to 4 percent) water;
- (b) carbon dioxide (to balance; typically at least 30 percent);
- (c) surfactant (preferably from 0.1 or .5 percent to 5 or 10 percent total, which may be comprised of one or more different surfactants); and
- (d) from 0.1 to 50 percent (more preferably 1, 2 or 4 percent to 30 percent) of an organic co-solvent.

Percentages herein are expressed as percentages by weight unless otherwise indicated.

The composition is provided in liquid form at ambient, or room, temperature, which will generally be between zero and 50° Centigrade. The composition is held at a pressure that maintains it in liquid form within the specified temperature range. The cleaning step is preferably carried out with the composition at ambient temperature.

The organic co-solvent is, in general, a hydrocarbon co-solvent. Typically the co-solvent is an alkane co-solvent, with C<sub>10</sub> to C<sub>20</sub> linear, branched, and cyclic alkanes, and mixtures thereof (preferably saturated) currently preferred. The organic co-solvent preferably has a flash point above 140°F, and more preferably has a flash point above 170°F. The organic co-solvent may be a mixture of compounds, such as

5

10

15

20

25

30

4

mixtures of alkanes as given above, or mixtures of one or more alkanes. Additional compounds such as one or more alcohols (e.g., from 0 or 0.1 to 5% of a C1 to C15 alcohol (including diols, triols, etc.)) different from the organic co-solvent may be included with the organic co-solvent.

Examples of suitable co-solvents include, but are not limited to, aliphatic and aromatic hydrocarbons, and esters and ethers thereof, particularly mono and di-esters and ethers (e.g., EXXON ISOPAR L, ISOPAR M, ISOPAR V, EXXON EXXSOL, EXXON DF 2000, CONDEA VISTA LPA-170N, CONDEA VISTA LPA-210, cyclohexanone, and dimethyl succinate), alkyl and dialkyl carbonates (e.g., dimethyl carbonate, dibutyl carbonate, di-t-butyl dicarbonate, ethylene carbonate, and propylene carbonate), alkylene and polyalkylene glycols, and ethers and esters thereof (e.g., ethylene glycol-n-butyl ether, diethylene glycol-n-butyl ethers, propylene glycol methyl ether, dipropylene glycol methyl ether, tripropylene glycol methyl ether, and dipropylene glycol methyl ether acetate), lactones (e.g., (gamma)butyrolactone, (epsilon)caprolactone, and (delta) dodecanolactone), alcohols and diols (e.g., 2-propanol, 2-methyl-2-propanol, 2-methoxy-2-propanol, 1-octanol, 2-ethyl hexanol, cyclopentanol, 1,3-propanediol, 2,3-butanediol, 2-methyl-2,4-pentanediol) and polydimethylsiloxanes (e.g., decamethyltetrasiloxane, decamethylpentasiloxane, and hexamethyldisloxane), etc.

Any surfactant can be used to carry out the present invention, including both surfactants that contain a CO<sub>2</sub>-philic group (such as described in PCT Application WO96/27704) linked to a CO<sub>2</sub>-phobic group (e.g., a lipophilic group) and (more preferably) surfactants that do not contain a CO<sub>2</sub>-philic group (i.e., surfactants that comprise a hydrophilic group linked to a hydrophobic (typically lipophilic) group). A single surfactant may be used, or a combination of surfactants may be used.

Numerous surfactants are known to those skilled in the art. See, e.g., McCutcheon's Volume 1: Emulsifiers & Detergents (1995 North American Edition) (MC Publishing Co., 175 Rock Road, Glen Rock, NJ 07452). Examples of the major surfactant types that can be used to carry out the present invention include the: alcohols, alkanolamides, alkanolamines, alkylaryl sulfonates, alkylaryl sulfonic acids, alkylbenzenes, amine acetates, amine oxides, amines, sulfonated amines and amides, betaine derivatives, block polymers, carboxylated alcohol or alkylphenol ethoxylates.

5

10

15

20

25

30

5

carboxylic acids and fatty acids, diphenyl sulfonate derivatives, ethoxylated alcohols, ethoxylated alkylphenols, ethoxylated amines and/or amides, ethoxylated fatty acids, ethoxylated fatty esters and oils, fatty esters, fluorocarbon-based surfactants, glycerol esters, glycol esters, hetocyclic-type products, imidazolines and imidazoline derivatives, isethionates, lanolin-based derivatives, lecithin and lecithin derivatives, lignin and lignin deriviatives, maleic or succinic anhydrides, methyl esters, monoglycerides and derivatives, olefin sulfonates, phosphate esters, phosphorous organic derivatives, polyethylene glycols, polymeric (polysaccharides, acrylic acid, and acrylamide) surfactants, propoxylated and ethoxylated fatty acids alcohols or alkyl phenols, protein-based surfactants, quaternary surfactants, sarcosine derivatives, silicone-based surfactants, soaps, sorbitan derivatives, sucrose and glucose esters and derivatives, sulfates and sulfonates of oils and fatty acids, sulfates and sulfonates, ethoxylated alkylphenols, sulfates of alcohols, sulfates of ethoxylated alcohols, sulfates of fatty esters, sulfonates of benzene, cumene, toluene and xylene, sulfonates of condensed naphthalenes, sulfonates of dodecyl and tridecylbenzenes, sulfonates of naphthalene and alkyl naphthalene, sulfonates of petroleum, sulfosuccinamates, sulfosuccinates and derivatives, taurates, thio and mercapto derivatives, tridecyl and dodecyl benzene sulfonic acids, etc.

Additional examples of surfactants that can be used to carry out the present invention include alcohol and alkylphenol polyalkyl ethers(e.g., TERGITOL 15-S-3<sup>TM</sup> secondary alcohol ethoxylate, TRITON X-207<sup>TM</sup> dinonylphenol ethoxylate, NEODOL 91-2.5<sup>TM</sup> primary alcohol ethoxylate, RHODASURF BC-410<sup>TM</sup> isotridecyl alcohol ethoxylate, RHODASURF DA-630<sup>TM</sup> tridecyl alcohol ethoxylate) alkylaryl carbonates, including salts and derivatives thereof (e.g., acetic acid, MARLOWET 4530™ dialkylphenol polyethylene glycol acetic acid, MARLOWET 1072™ alkyl polyethylene glycol ether acetic acid), alkoxylated fatty acids (e.g., NOPALCOL 1-TW™ diethylene glycol monotallowate, TRYDET 2600™ polyoxyethylene (8) monostearate), alkylene oxide block copolymers (e.g., PLURONICTM and TETRONICTM products), acetylenic alcohols and diols (e.g., SURFYNOLTM and DYNOL<sup>TM</sup> products), mono- and di-esters of sulfosuccinic acid (e.g., AEROSOL OTTM sodium dioctyl sulfosuccinate, AEROSOL IB-45TM sodium diisobutyl sulfosuccinate, MACKANATE DC-50TM dimethicone copolyol disodium

5

10

15

20

25

30

6

sulfosuccinate, SOLE TERGE-8<sup>TM</sup> oleic acid isopropanolamide monoester of sodium sulfosuccinate), sulfosuccinamic acid and esters thereof (e.g. AEROSOL 18TM disodium-N-octadecyl sulfosucciniamate, AEROSOL 22TM tetrasodium N-(1,2dicarboxyethyl)-N octadecyl sulfosuccinamate) sorbitan esters including derivatives thereof (e.g., SPAN 80<sup>TM</sup> sorbitan monoleate, ALKAMULS 400-DO<sup>TM</sup> sorbitan dioleate, ALKAMULS STO™ sorbitan trioleate, TWEEN 81™ polyoxyethylene (5) sorbitan monoleate, TWEEN 21<sup>TM</sup> polyoxyethylene (4) sorbitan monolaurate), isothionates including derivatives thereof (e.g., GEROPON AC-270<sup>TM</sup> sodium cocoyl isothionate), polymeric alkylaryl compounds and lignins, including derivatives thereof (e.g., LIGNOSITE 50™ calcium lignosulfonate), alkylaryl sulfonic acids and salts thereof (e.g., CALIMULSE EM-99TM branched dodecylbenzene sulfonic acid, WITCONATE C-50H™ sodium dodecylbenzene sulfonate, WITCONATE P10-59™ amine salt of dodecylbenzene sulfonate), sulfonated amines and amides (e.g., CALIMULSE PRSTM isopropylamine sulfonate), Betaine and sultaine derivatives, and salts thereof (e.g., lauryl sulfobetaine, dodecyldimethyl(3-sulfopropyl)ammonium hydroxide, FOAMTAIN CAB-ATM cocamidopropyl betaine ammonium salt, FOAMTAINE SCAB<sup>TM</sup> cocamidopropyl hydroxy sultaine), e.g., imidazolines including derivatives thereof (e.g., MONOAZOLINE OTM substituted imidazoline of oleic acid, MONOAZOLINE TTM substituted imidazoline of Tall Oil), oxazolines including derivatives thereof (e.g., ALKATERGE ETM oxazoline derivative, ALKATERGE T-IV™ ethoxylated oxazoline derivative), carboxylated alcohol or alkylphenol ethoxylates including derivatives thereof (e.g., MARLOSOL OL7™ oleic acid polyglycol ester), diphenyl sulfonates including derivatives thereof (e.g., DOWFAX<sup>TM</sup> detergent diphenyl oxide disulfonate, DOWFAX<sup>TM</sup> dry detergent: sodium n-hexadecyl diphenyl oxide disulfonate, DOWFAX<sup>TM</sup> Dry hydrotrope: sodium hexyl diphenyloxide disulfonate) fluorinated surfactants (e.g., FLUORAD FC-120<sup>™</sup> ammonium perfluoroalkyl sulfonate, FLUORAD FC-135<sup>™</sup> fluoroalkyl quaternary ammonium iodides, FLUORAD FC-143<sup>TM</sup> ammonium perfluoroalkyl carboxylates), lecithins including lecithin derivatives (e.g., ALCOLEC BSTM soy phosphatides), phosphate esters (e.g., ACTRAFOS SA-216<sup>TM</sup> aliphatic phosphate ester, ACTRAFOS 110™ phosphate ester of complex aliphatic hydroxyl compound, CHEMPHOS TC-310<sup>™</sup> aromatic phosphate ester, CALGENE PE-112N<sup>™</sup>

5

10

15

20

25

30

7

phosphated mono- and diglycerides), sulfates and sulfonates of fatty acids (e.g., ACTRASOL PSR™ sulfated castor oil, ACTRASOL SR75™ sulfated oleic acid), sulfates of alcohols (e.g., DUPONOL CTM sodium lauryl sulfate, CARSONOL SHSTM sodium 2-ethyl-1-hexyl sulfate, CALFOAM TLS-40™ triethanolamine lauryl sulfate), sulfates of ethoxylated alcohols (e.g., CALFOAM ES-301™ sodium lauryl derivatives thereof (e.g., ether sulfate), amines, including salts and Tris(hydroxymethyl)aminomethane, ARMEEN<sup>TM</sup> primary alkylamines, ARMAC HT<sup>™</sup> acetic acid salt of N-alkyl amines) amide sulfonates (e.g., GEROPON TC-42<sup>™</sup> sodium N-coconut acid-N-methyl taurate, GEROPON TC 270™ sodium cocomethyl tauride), quaternary amines, including salts and derivatives thereof (e.g., ACCOSOFT 750<sup>TM</sup> methyl bis (soya amidoethyl)-N-polyethoxyethanol quaternary ammonium methyl sulfate, ARQUAD™ N-alkyl trimethyl ammonium chloride, ABIL QUAT 3272<sup>TM</sup> diquaternary polydimethylsiloxane), amine oxides (e.g., AMMONYX CO<sup>TM</sup> cetyl dimethylamine oxide, AMMONYX SO™ stearamine oxide), esters of glycerol, sucrose, glucose, sarcosine and related sugars and hydrocarbons including their derivatives (e.g., GLUCATE DO™ methyl glucoside dioleate, GLICEPOL 180™ glycerol oleate, HAMPOSYL AL-30™ ammonium lauroyl sarcosinate, HAMPOSYL Мтм N-myristoyl sarcosine, **CALGENE**  $CC^{TM}$ propylene glycol dicaprylate/dicaprate), polysaccharides including derivatives thereof (e.g., GLUCOPON 225 DK<sup>TM</sup> alkyl polysaccharide ether), protein surfactants (e.g., AMITER LGS-2<sup>™</sup> dioxyethylene stearyl ether diester of N-lauroyl-L-glutamic acid, AMISOFT CATM cocoyl glutamic acid, AMISOFT CS 11TM sodium cocoyl glutamate, MAYTEIN KTS™ sodium/TEA lauryl hydrolyzed keratin, MAYPON 4CTM potassium cocoyl hydrolyzed collagen), and including thio and mercapto derivatives of the foregoing (e.g., ALCODET<sup>TM</sup> polyoxyethylene thioether, BURCO TME<sup>TM</sup> ethoxylated dodecyl mercaptan), etc.

Thus the present invention may be carried out using conventional surfactants, including but not limited to the anionic or nonionic alkylbenzene sulfonates, ethoxylated alkylphenols and ethoxylated fatty alcohols described in Schollmeyer German Patent Application DE 39 04514 A1, that are not soluble in liquid carbon dioxide and which could not be utilized in the invention described in U.S. Patent No. 5,683,473 to Jureller et al. or U.S. Patent No. 5,683,977 to Jureller et al.

As will be apparent to those skilled in the art, numerous additional ingredients can be included in the dry-cleaning composition, including detergents, bleaches, whiteners, softeners, sizing, starches, enzymes, hydrogen peroxide or a source of hydrogen peroxide, fragrances, etc.

In practice, in a preferred embodiment of the invention, an article to be cleaned and a liquid dry cleaning composition as given above are combined in a closed drum. The liquid dry cleaning composition is preferably provided in an amount so that the closed drum contains both a liquid phase and a vapor phase (that is, so that the drum is not completely filled with the article and the liquid composition). The article is then agitated in the drum, preferably so that the article contacts both the liquid dry cleaning composition and the vapor phase, with the agitation carried out for a time sufficient to clean the fabric. The cleaned article is then removed from the drum. The article may optionally be rinsed (for example, by removing the composition from the drum, adding a rinse solution such as liquid CO<sub>2</sub> (with or without additional ingredients such as water, co-solvent, etc.) to the drum, agitating the article in the rinse solution, removing the rinse solution, and repeating as desired), after the agitating step and before it is removed from the drum. The dry cleaning compositions and the rinse solutions may be removed by any suitable means, including both draining and venting.

Any suitable cleaning apparatus may be employed, including both horizontal drum and vertical drum apparatus. When the drum is a horizontal drum, the agitating step is carried out by simply rotating the drum. When the drum is a vertical drum it typically has an agitator positioned therein, and the agitating step is carried out by moving (e.g., rotating or oscillating) the agitator within the drum. A vapor phase may be provided by imparting sufficient shear forces within the drum to produce cavitation in the liquid dry-cleaning composition. Finally, in an alternate embodiment of the invention, agitation may be imparted by means of jet agitation as described in U.S. Patent No. 5,467,492 to Chao et al., the disclosure of which is incorporated herein by reference. As noted above, the liquid dry cleaning composition is preferably an ambient temperature composition, and the agitating step is preferably carried out at ambient temperature, without the need for associating a heating element with the cleaning apparatus.

9

The present invention is explained in greater detail in the following nonlimiting examples.

## **EXAMPLES 1-2**

This example shows that various CO<sub>2</sub> detergent formulations show a significantly enhanced cleaning effect over a commercial perchloroethylene ("perc") dry cleaning system. Small (2" x 2") swatches of various delicate (often "dry clean only") cloth were uniformly stained and run in both perc and CO<sub>2</sub> cleaning systems. Two CO<sub>2</sub> cleaning systems were employed, as follows:

FIRST:

5

0.5% X-207 (a commercial detergent from Union Carbide—di-nonyl phenyl ethoxylate with a hydrophobic-lipophilic balance (HLB) of about 10.5);

0.5% PDMS-g<sub>3</sub>-PEG (polydimethyl siloxane-graft-polyethylene glycol copolymer) (500 g/mol PDMS with 350 g/mol peg grafts ca. 50 wt% PEG);

1% Span<sup>TM</sup> 80 (a commercial sorbitan ester surfactant from ICI);

0.5% isopropanol;

0.2% water;

30% Isopar<sup>TM</sup> M (a commercial hydrocarbon solvent manufactured by EXXON); and

CO<sub>2</sub> to balance; or

#### SECOND:

25

20

15

1% X-207;

1% Span<sup>TM</sup> 80;

1% isopropanol;

0.2% water;

30% Isopar<sup>TM</sup> M; and

CO<sub>2</sub> to balance.

The second system above is currently preferred.

10

At a temperature of 22°C to 27°C, the formulation and cloth was added to the test vessel. The test vessel was presurized with liquid CO<sub>2</sub> to 800-900 psi, with the total liquid volume equal to about half the vessel volume. The cloth was washed with agitation for ten minutes. To rinse, the liquid CO<sub>2</sub> was vented, the cloth spun for five minutes, liquid CO<sub>2</sub> was again added and pressurized to 800 to 900 psi until the vessel was one half full, and the cloth again agitated for five minutes. The rinse cycle (vent, spin, agitate) was repeated, the system vented and the cloth removed.

Control "perc" samples were run in perchloroethylene using a standard loading of Fabritech<sup>TM</sup> detergent and sizing, at a local commrcial dry cleaner under normal operating conditions. In each case the stained samples of cloth were washed in one of the CO<sub>2</sub> mixtures described above, followed by extraction and rinse with clean CO<sub>2</sub>.

The following cloth samples were run:

1. White linen suiting

- 2. Acetate taffeta
- 3. Silk twill

5

10

15

20

25

- 4. 100% wool flannel
- 5. Bright filament viscose twill
- 6. Texturized nylon 6,6 stretch fabric
- 7. Texturized stretch Dacron<sup>TM</sup>

Results are given in **Table 1** below. These data show that CO<sub>2</sub>-based dry cleaning formulations of the present invention have an enhanced cleaning effect as compared to a commercial PERC dry cleaning system.

TABLE 1.

Cloth	Stain	PERC result	CO2 result
2, 4, 1	French salad	slight residue remaining	visually clean, no
	dressing		residue
1, 2, 3, 4,	Spaghetti	majority of stain remaining	slight residue
6	sauce		remaining
5	Tea	over ½ of residue	slight residue
		remaining, plus darkening	remaining, no 'ring'
		of 'ring' around the stained	apparent
		area	
2	Tea	slight residue remaining	visually clean, no
			residue
5	Blackberry	slight residue remaining	visually clean, no
	juice		residue
4, 5, 7	Grass	slight residue remaining	minute residue
			remaining <sup>1</sup>
4	Coke <sup>TM</sup> cola	½ of stain remaining	minute residue
	beverage		remaining
4	Coffee	½ of stain remaining	minute residue
			remaining
1	Egg	no significant removal of	slight residue
		stain, slight color change of	remaining
		stain	
1, 2, 4, 6	taco sauce	majority of stain remaining	slight residue
			remaining

5 By "minute" is meant significantly less than the perc result.

#### **EXAMPLE 3**

An additional liquid carbon dioxide cleaning system, or wash fluid, that can be used in the methods described herein, is a mixture that contains:

- 2.86% ISOPAR M™ organic solvent;
- 1.23% DPMA (dipropyleneglycol menomethyl ether acetate);
- 0.56% TERGITOL 15-S-3™ (Union Carbide secondary alcohol ethoxylate with an HLB of 8.3);
  - 0.28% water;

15

0.05% TRITON GR-7M™ (commercial detergent from Union Carbide--sodium dioctylsulfosuccinate in petroleum distillates);

12

0.02% TRITON RW-20™ (commercial detergent from Union Carbide--ethoxylated alkylamines); and liquid carbon dioxide to balance.

## 5 EXAMPLE 4

An additional example of a liquid dry cleaning system useful for carrying out the present invention is a a mixture that contains:

- 2.80% DPM (dipropyleneglycol monomethyl ether);
- 1.20% hexylene glycol;
- 0.50% TERGITOL 15-S-3™ detergent;
- 0.50% water; and

liquid carbon dioxide to balance.

#### **EXAMPLE 5**

An additional example of a liquid dry cleaning system useful for carrying out the present invention is a mixture that contains:

- 2.80% DPM;
- 1.20% hexylene glycol;
- 0.50% TERGITOL 15-S-3™ detergent;
- 20 0.40% water;

10

0.10% C-300<sup>™</sup> (commercial detergent formulation from ADCO containing quaternary amines and optical brighteners); and carbon dioxide to balance.

# 25 EXAMPLE 6

An additional example of a liquid dry cleaning system useful for carrying out the present invention is a mixture that contains:

- 2.80% ISOPAR M<sup>TM</sup> organic solvent;
- 1.20% DPMA;
- 30 0.50% water;
  - 0.35% EMCOL 4500™ (a commercial detergent from Witco—70% dioctyl sodium sulfonate, 30% ethanol, 10% water)

13

0.15% ACTRAFOS 110™ (Commercial detergent from Actrachem—phosphate ester of complex aliphatic hydroxyl compound); and liquid carbon dioxide to balance.

5 EXAMPLE 7

An additional example of a liquid carbon dioxide dry cleaning system that can be used to carry out the present invention is a mixture that contains:

2.80% TPM (tripropyleneglycol monomethyl ether);

1.20% propylene carbonate;

0.50% PLURONIC L31™ (commercial detergent from BASF—polyethylene oxide-polypropylene oxide block copolymer);

0.40% water;

0.10% lauryl sulfobetaine; and

liquid carbon dioxide to balance.

15

10

#### **EXAMPLE 8**

An additional example of a liquid carbon dioxide dry cleaning system that can be used to carry out the present invention is a mixture that contains:

2.80% ISOPAR M<sup>TM</sup> organic solvent;

20 1.20% DPMA;

0.60% PLURONIC L31™ detergent;

0.60% water;

0.10% cyclohexanol; and

liquid carbon dioxide to balance.

25

30

#### **EXAMPLE 9**

An additional example of a liquid carbon dioxide dry cleaning system that can be used to carry out the present invention is a mixture that contains:

4.0% ISOPAR M<sup>TM</sup> organic solvent;

0.7% sodium dioctylsulfosuccinate;

0.3% water; and

liquid carbon dioxide to balance.

14

#### **EXAMPLE 10**

An additional example of a liquid carbon dioxide dry cleaning system that can be used to carry out the present invention is a mixture that contains:

4.00% ISOPAR M™ organic solvent;

0.62% WITCONATE P1059™ (commercial detergent of Witco—isopropylamine salt of dodecylbenzene sulfonate);

0.35% water;

0.03% TRIS™ pH buffer (tris[hydroxymethyl]aminomethane); and liquid carbon dioxide to balance.

#### **EXAMPLE 11**

An additional example of a liquid carbon dioxide dry cleaning system that can be used to carry out the present invention is a mixture that contains:

4.2% ISOPAR M<sup>TM</sup> organic solvent;

0.24% water;

0.196% TRITON™ RW-20 (commercial detergent available from Union Carbide; a secondary amine ethoxylate);

0.048% TRITON™ GR-7M detergent (a commercial detergent of Union Carbide; sodium dioctyl sulfosuccinate in aromatic and aliphatic hydrocarbons)

0.48% TERGITOL™ 15-S-3 detergent (a commercial detergent of Union Carbide; a secondary alcohol ethoxylate); and liquid carbon dioxide to balance.

25

30

5

10

15

20

#### **EXAMPLE 12**

An additional example of a liquid carbon dioxide dry cleaning system that can be used to carry out the present invention is a mixture that contains:

3.07% ISOPAR M<sup>TM</sup> organic solvent;

. . . .

1.32% DPMA (diopropylene glycol monomethyl ether acetate);

0.087% water;

.15

0.023% TRITON™ GR-7M detergent (a commercial detergent of Union Carbide; sodium dioctyl sulfosuccinate in aromatic and aliphatic hydrocarbons)

0.5% TERGITOL™ 15-S-3 detergent (a commercial detergent of Union Carbide; a secondary alcohol ethoxylate); and liquid carbon dioxide to balance.

The liquid dry cleaning systems of Examples 11 and 12 are currently preferred.

5

The foregoing is illustrative of the present invention, and is not to be construed as limiting thereof. The invention is defined by the following claims, with equivalents of the claims to be included therein.

16

#### That which is claimed is:

5

10

20

1. A method for dry-cleaning garments or fabrics in carbon dioxide, comprising:

contacting a garment or fabric article to be cleaned with a liquid dry cleaning composition for a time sufficient to clean the article, said liquid dry-cleaning composition comprising a mixture of carbon dioxide, water, surfactant, and an organic co-solvent;

wherein said surfactant does not contain a CO<sub>2</sub>-philic group; and then separating the article from the liquid dry cleaning composition.

- 2. A method according to claim 1, wherein said liquid dry cleaning composition is at a temperature of 0° C to 30° C.
- 3. A method according to claim 1, wherein said organic co-solvent has a flash point above 140°F.
  - 4. A method according to claim 1, wherein said organic co-solvent has a flash point above 170°F.
  - 5. A method according to claim 1, wherein said organic co-solvent has a flash point above 200°F.
- 6. A method according to claim 1, wherein said organic co-solvent is a hydrocarbon co-solvent.
  - 7. A method according to claim 1, wherein said organic co-solvent is an alkane co-solvent.
- 8. A method according to claim 7, said liquid dry cleaning composition further comprising an alcohol.
  - 9. A method according to claim 1, wherein said contacting step is carried out by jet agitation.

5

10

15

20

30

PCT/US98/17730

- 10. A method for dry-cleaning garments or fabrics in carbon dioxide, comprising:
  - (a) combining a garment or fabric article to be cleaned and a liquid dry cleaning composition in a closed drum so that said closed drum contains both a liquid phase and a vapor phase, said liquid dry cleaning composition comprising a mixture of liquid carbon dioxide, water, surfactant, and a hydrocarbon co-solvent;
  - (b) agitating said article in said drum so that said article contacts both said liquid dry cleaning composition and said vapor phase for a time sufficient to clean said article; and then
    - (c) removing the cleaned article from said drum.
- 11. A method according to claim 10, wherein said drum is a horizontal rotating drum, and said agitating step is carried out by rotating said drum.

12. A method according to claim 10, wherein said drum is a vertical drum having an agitator positioned therein, and said agitating step is carried out by moving said agitator.

- 13. A method according to claim 10, wherein said liquid dry cleaning composition is a room-temperature composition and said agitating step is carried out at a temperature of 0° C to 30° C.
- 14. A method according to claim 10, wherein said surfactant contains a CO<sub>2</sub>-philic group.
  - 15. A method according to claim 10, wherein said surfactant does not contain a CO<sub>2</sub>-philic group.
  - 16. A method according to claim 10, wherein said organic co-solvent has a flash point above 140°F.
    - 17. A method according to claim 10, wherein said organic co-solvent has a flash point above 170°F.

- 18. A method according to claim 10, wherein said organic co-solvent has a flash point above 200°F.
- 5 19. A method according to claim 10, wherein said organic co-solvent is an alkane co-solvent.
  - 20. A method according to claim 10, said liquid dry cleaning composition further comprising an alcohol.

10

- 21. A liquid dry-cleaning composition, useful for carrying out dry cleaning in carbon dioxide at or about room temperature and vapor pressure, said composition comprising:
  - (a) from 0.1 to 10 percent water;
- (b) carbon dioxide;
  - (c) from 0.1 to 10 percent surfactant; and
  - (d) from .01 to 50 percent of an organic co-solvent; wherein said surfactant does not contain a CO<sub>2</sub>-philic group.

20

25

15

- 22. A liquid dry-cleaning composition according to claim 21, said composition comprising:
  - (a) from 0.1 to 4 percent water;
  - (b) carbon dioxide;
  - (c) from 0.5 to 5 percent surfactant; and
  - (d) from 4 to 30 percent of an organic co-solvent.
- 23. A composition according to claim 21, wherein said organic co-solvent has a flash point above 140°F.

30

24. A composition according to claim 21, wherein said organic co-solvent has a flash point above 170°F.

19

- 25. A composition according to claim 21, wherein said organic co-solvent has a flash point above 200°F.
- 26. A composition according to claim 21, wherein said organic co-solvent is a hydrocarbon co-solvent.
  - 27. A composition according to claim 21, wherein said organic co-solvent is an alkane co-solvent.
- 28. A composition according to claim 21, further comprising an alcohol.

# INTERNATIONAL SEARCH REPORT

Int. Jonal Application No PCT/US 98/17730

A. CLASSI IPC 6	FICATION OF SUBJECT MATTER D06L1/00 C11D1/00 D06L	_1/02 DO	6L1/04	D06L1/12
According to	o International Patent Classification (IPC) or to both national c	classification and IPC		
***********	SEARCHED			
Minimum do IPC 6	ocumentation searched (classification system followed by clase DO6L DO6F C11D	ssification symbols)		
Documentat	tion searched other than minimum documentation to the exter	nt that such document	s are included in	the fields searched
Electronic d	ata base consulted during the international search (name of	data base and, where	practical, search	terms used)
С. БОСИМ	ENTS CONSIDERED TO BE RELEVANT			······································
Category ?	Citation of document, with indication, where appropriate, of	f the relevant passage	s	Relevant to claim No.
X	WO 97 16264 A (UNIV NORTH CAR 9 May 1997 see page 12, line 32 - line 3 1,8,15,16,18; example 50			10-14, 16-20
х	DE 39 04 514 A (OEFFENTLICHE UND TEXTILINSTITUT FUER VERTR 23 August 1990 cited in the application see page 3, line 51 - page 4,	RAGFORSCHUNG		1,2,10, 11,13,15
А	see page 4, line 19 - line 26 example 2		2;	3-8
		-/		
•				
X Furth	her documents are listed in the continuation of box C.	X Pate	nt family member	s are listed in annex.
° Special ca	stegories of cited documents :			
"A" docume	ent defining the general state of the art which is not	or priority	y date and not in o	ter the international filing date conflict with the application but nciple or theory underlying the
	lered to be of particular relevance document but published on or after the international late	invention "X" document	i of particular relev	ance; the claimed invention
"L" docume which	ent which may throw doubts on priority claim(s) or is cited to establish the publication date of another	involve a	n inventive step w	of cannot be considered to the considered to the document is taken alone ance; the claimed invention
_	n or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or means	cannot b	e considered to in nt is combined with	volve an inventive step when the none or more other such docu- eing obvious to a person skilled
"P" docume	ant published prior to the international filing date but nan the priority date claimed	in the art		,
Date of the	actual completion of the international search	Date of n	nailing of the interr	national search report
2	3 November 1998	10,	/12/1998	
Name and n	nailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2	Authorize	d officer	
NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016 Saunders, T				

1

# INTERNATIONAL SEARCH REPORT

Int. sional Application No PCT/US 98/17730

		PC1/US 98/1//30
	ation) DOCUMENTS CONSIDERED TO BE RELEVANT	
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 96 27704 A (UNILEVER) 12 September 1996	10-14, 16-28
Α	see page 36, line 26 - page 37, line 35; claims 1,5; example 5 & US 5 683 473 A cited in the application & US 5 683 977 A cited in the application	1,2,9
Y	EP 0 518 653 A (CLOROX CO) 16 December 1992 see page 3, line 40 - page 4, line 1; claims 1,2,4; table I	1-28
Υ .	EP 0 679 753 A (HUGHES AIRCRAFT CO)	1-13,
A	2 November 1995 see column 4, line 34 - line 46 see column 7, line 43 - column 8, line 35; claims 1,7,10 & US 5 467 492 A cited in the application	15-20 21,22
A	WO 94 01613 A (CLOROX CO) 20 January 1994	1-8, 10-13, 16-28
	see page 7, line 6 - page 8, line 2 see page 10, line 13 - line 23; claim 1 	
A	EP 0 732 154 A (LINDE AG) 18 September 1996	1,2,10, 11,13, 15,21,22
	see column 3, line 36 - line 41; claims 1,4,9,10	
A	DATABASE TEXTILE INSTITUTE OF TEXTILE TECHNOLOGY, CHARLOTTESVILLE, VA, US SOUTHERN TEXTILE NEWS (VOL.53, NO 33:12), 25 August 1997 "NCSU COLLEGE OF TEXTILES' RESEARCHER DEVELOPS ENVIRONMENTALLY SOUND CO2 DRY CLEANING" XP002085400 see abstract	1,10,14, 15,21,22
A	DESIMONE, JOSEPH M; CANELAS, DORIAN A: "DESIGN AND UTILIZATION OF SURFACTANTS FOR CO2" 213TH ACS NATIONAL MEETING, 13 - 17 April 1997, XP002085399 SAN FRANCISCO, CA see abstract	1,10,14, 15,21,22
A .	"DESIGN AND UTILIZATION OF SURFACTANTS FOR CO2" 213TH ACS NATIONAL MEETING, 13 - 17 April 1997, XP002085399 SAN FRANCISCO, CA	

# INTERNATIONAL SEARCH REPORT

information on patent family members

Inte Jonal Application No PCT/US 98/17730

Patent document cited in search report		Publication date		atent family nember(s)	Publication date	
WO	9716264	Α	09-05-1997	US AU	5783082 A 7525896 A	
DE	3904514	A	23-08-1990	NONE		
WO	9627704	Α	12-09-1900	US US	5683977 A 5676705 A	
				AU CA	4942996 A 2211412 A	23-09-199
				EP FI	0813628 A 973603 A	
				us	5683473 A	04-11-199
EP	0518653	Α	16-12-1992	US	5279615 A	18-01-199
				AT AU	127547 T 661314 B	15-09-199 20-07-199
				AU	1815792 A	17-12-199
				CA DE	2070760 A 69204567 D	15-12-199 12-10-199
				DE	69204567 T	01-02-199
				ES	2078659 T	16-12-199
				JP	5202388 A	10-08-199
EP	0679753	Α	02-11-1995	US	5467492 A	21-11-199
				CN JP	1119684 A 8052297 A	03-04-199 27-02-199
WO	9401613	Α	20-01-1900	US	5267455 A	07-12-199
				AU	666037 B	25-01-199
				AU CA	4672593 A 2139950 A	31-01-199 20-01-199
				EP	0651831 A	10-05-199
				JP	7508904 T	05-10-199
				US 	5412958 A	09-05-199
EP	0732154	Α	18-09-1996	DE	19509573 A	19-09-199
				US	5759209 A	02-06-199